



PRIMARY COLLECTORS

	<u>OPTION 1 (SN=3.50)</u>	<u>OPTION 2 (SN=3.50)</u>	<u>OPTION 3 (SN=3.46)</u>
STRUCTURAL COURSE:	2" TYPE S-III ASPHALTIC CONCRETE (TACK BETWEEN COURSES)	2 1/2" TYPE S-1 ASPHALTIC CONCRETE (TACK BETWEEN COURSES)	2 1/2" TYPE S-1 ASPHALTIC CONCRETE (TACK BETWEEN COURSES)
BASE:	10" LIMEROCK, PRIMED, COMPACTED TO 98% OF AASHTO T-180	8" ABC-3	6" ABC-3, AND 4" LIMEROCK, PRIMED, COMPACTED TO 100% OF ASTM-1557
SUBGRADE:	12" STABILIZED LBR-40	(NOT APPLICABLE)	(NOT APPLICABLE)

CITY STREETS

	<u>OPTION 1 (SN=3.06)</u>	<u>OPTION 2 (SN=3.06)</u>	<u>OPTION 3 (SN=3.02)</u>
STRUCTURAL COURSE:	2" TYPE S-III ASPHALTIC CONCRETE (TACK BETWEEN COURSES)	1 1/2" TYPE S-1 ASPHALTIC CONCRETE (TACK BETWEEN COURSES)	1 1/2" TYPE S-1 ASPHALTIC CONCRETE (TACK BETWEEN COURSES)
BASE:	10" LIMEROCK, PRIMED, COMPACTED TO 98% OF AASHTO T-180	8" ABC-3	6" ABC-3, AND 4" LIMEROCK, PRIMED, COMPACTED TO 100% OF ASTM-1557
SUBGRADE:	12" STABILIZED LBR-40	(NOT APPLICABLE)	(NOT APPLICABLE)

REVISED: SEPT-2009	GENERAL CONSTRUCTION - ASPHALT PAVEMENT SECTION	STANDARD DETAIL
ISSUED: SEPT - 2009	CITY OF WEST PALM BEACH ENGINEERING SERVICES DEPT.	GC-5